Phone: (949) 458-7277

Fax: (949) 458-0826

Home

About

Where to Order

**Power Supplies** 

**Replacement Parts** 



# **Linear Power Supplies with Meters**



# **Features and Specifications**

- SOLID STATE ELECTRONICALLY REGULATED
- FOLD BACK CURRENT LIMITING Protects Power Supply from excessive current and continuous shorted output
- CROWBAR OVER VOLTAGE PROTECTION ON ALL MODELS
- MAINTAIN REGULATION AND LOW RIPPLE at low line input Voltage
- THREE CONDUCTOR POWER CORD
- HEAVY DUTY HEAT SINK

- INPUT VOLTAGE: 105-125VAC
- OUTPUT VOLTAGE: 13.8VDC ±0.05 volts
- INTERNALLY ADJUSTABLE VOLTAGE (11-15VDC)
- RIPPLE: LESS THAN 5MV PEAK TO PEAK (full load and low line)
- LOAD REGULATION: 0.08% from 0 to Full Continuous Load
- EFFICIENCY: 77%
- OPERATING TEMP: -10 to 55°C
- ANDERSON POWER POLES INSTALLED IN -AP MODELS
- 220V MODELS AVAILABLE BY SPECIAL ORDER

### RS-20M-AP



- CONTINUOUS DUTY: 16 Amps
- ICS\*: 20 Amps
- DIMENSIONS: 5 x 9 x 101/2"
- SHIPPING WEIGHT: 18 lbs
- FUSE: GMC 5A
- POWER TERMINALS:
  - 1/4"-20 Screw Type
- AC CURRENT DRAW IDLE: 215mA

## RS-35M-AP



- CONTINUOUS DUTY: 25 Amps
- ICS\*: 35 Amps
- DIMENSIONS: 5 x 11 x 11"
- SHIPPING WEIGHT: 27 lbs
- FUSE: AGC 8A
- POWER TERMINALS:
  - 1/4"-20 Screw Type
- AC CURRENT DRAW IDLE: 230mA

#### FULL LOAD: 3.4A

- FAN COOLED: No
- LED BACKLIT VOLT AND AMP **METERS**
- Anderson Power Poles available on model RS-20M-AP

# **METERS**

- FAN COOLED: No • LED BACKLIT VOLT AND AMP
- · Anderson Power Poles available

FULL LOAD: 5.7A

## on model RS-35M-AP

## **RS-50M**



- CONTINUOUS DUTY: 37 Amps
- ICS\*: 50 Amps
- DIMENSIONS: 6 x 13% x 11"
- SHIPPING WEIGHT: 46 lbs
- . FUSE: GMC 10A
- POWER TERMINALS:
  - 1/4"-20 Screw Type
- AC POWER DRAW IDLE: 316mA FULL LOAD: 8.2A
- FAN COOLED: No
- LED BACKLIT VOLT AND AMP **METERS**

### **RS-70M**



- CONTINUOUS DUTY: 57 Amps
- ICS\*: 70 Amps
- DIMENSIONS: 6 x 13% x 11"
- SHIPPING WEIGHT: 48 lbs
- FUSE: MDA 12A Ceramic
- POWER TERMINALS:
- AC CURRENT DRAW
- IDLE: 340mA FULL LOAD: 11.4A
- FAN COOLED: Yes
- LED BACKLIT VOLT AND AMP **METERS**

Follow



Address Contact

9 Autry astron@astroncorp.com Irvine, CA 92618 Phone: (949) 458-7277 USA Fax: (949) 458-0826

Hours: 7:00 - 5:00 Pacific Mon - Thurs

©2018 by Astron Corporation